

100 000 liters tank i rustfritt stål 304



714 000 SEK /st exkl moms

Additional information: PH glycerin; Electrical trace heating using external heating cables (no guarantee of functionality); Manhole diameter 600 mm (manhole cover may no longer exist); some residues of previous content

Volumetric volume (L): 100.000 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 60 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 80

Top: 5 mm

Bottom: 9 mm

Internal diameter tank: 2.900 mm

Cylinder height: 15.140 mm

SKU: 402539

Mer information



Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert
Maks. arbeidstemperatur: 60 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon:
Omrører: Nei
Total uttapping: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 100000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 15 140 mm
Innvendig diameter: 2900 mm

Tanktykkelse

Bunn: 9 millimeter
Topp: 5 mm



Mer

Isolert: Ja