

100 liters tank i syrefast 316



38 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe inside the tank (see pictures);

Volumetric volume (L): 100 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar



Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 25 L

Max Overpressure: 6 Bar

Max. working temperature: 140 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: clamp

Internal diameter tank: 495 mm

Cylinder height: 560 mm

Total height of tank: 1.250 mm

SKU: 481164



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: apotek; Påfyllingsrør inne i tanken (se bilder);

Omrører: Nei

Overtrykk: 3 barer

Total uttapping: Ja

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 100

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 560 mm

Innvendig diameter: 495 mm

Total høyde: 1250 mm



Mer

Varmeveksler: RVS 304

Isolert: Nei