100 liters tank i syrefast 316

168 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HICA
Additional information: delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options)*; Ra=<0.8µm
Volumetric volume (L): 100 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: yes

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket
Position HE: the complet cilinder
Height HE: 375 mm
Number of sections: 1
Water pressure HE: 3 Bar

Hydraulic test pressure: 4 Bar
Connection HE: 1" BSP
Working temperature HE cylinder: 130 °C
Heat exchanger: RVS 304
Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: yes
CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851

Total outlet valve: no, optional

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Agitator: no, optional
Top: 3 mm
Cylinder: 3 mm
Bottom: 3 mm

Cylinder: 2
Insulation body: yes
finish of the outer jacket: welded
Insulation thickness: 40
Distance from outlet to ground: 250 mm

Outer diameter tank: 580 mm
Cylinder height: 500 mm
Total height of tank: 1.350 mm
Empty weight tank: 90

SKU: 376439

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank:
Finish rustfritt stål: 2b
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 100 °C
Maksimal tetthet for produktet: 1200
Min. arbeidstemperatur: -10 °C
Mobil tank: Ja
Øvrig informasjon: leveres med næringsmiddelsertifikat; artikkelpris uten røreverk; valg mellom 2 ulike typer røreverk; se tilvalg; (Artikkelen kan også kjøpes uten tilvalg);
Øvrig informasjon2: Ra=<0,8µm
Omrører: Nei
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk 10
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 100

Utstyr

Flens for omrører: Ja
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 40 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304
Isolasjonsmateriale: Rockwool
Utvendig kledning: RVS 304

Tankdimensjoner

Sylinderhøyde: 500 mm
Mål utløp til bakken: 250 mm
Total høyde: 1350 mm
Ytre diameter: 580 mm

Varmevekslere

Tilkobling varmeveksler: 1" BSP
Arbeidstemperatur varmeveksler sylinder: 130 °C
Høyde varmeveksler: 375 mm
Hydraulisk prøvetrykk bunn: 4 barer
Hydraulisk prøvetrykk: 4 barer
Posisjon varmeveksler: den komplette sylinderen
Type varmeveksler på sylinder: dimple jakke
Vanntrykk varmeveksler: 3 barer

Tanktykkelse

Bunn: 3 mm
Sylinder: 3 mm
Topp: 3 mm

Tykkelse på ytterbekledning og isolasjon

Finish utvendig kappe: sveiset
Isolasjon kappe: Ja
Isolasjonsmateriale: Rockwool

Mer

Varmeveksler: RVS 304
Sylinder OW: 2
Isolasjonstykkelse OW: 40
Isolert: Ja
Vekt: 90

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor