1000 liters tank i syrefast 316

215 000 SEK /st exkl moms

Additional information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating the heating medium in the double jacket; Attention: The vessel is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; switch cabinet for the electric heaters available (temperature of the double jacket can be regulated via switch cabinet); 2 ball valves for the heating jacket are included in the scope of delivery; contrary to the information in the drawing, the inside of

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

the vessel is not polished
Volumetric volume (L): 1.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 0 - 1400

Power: 0,75
Cylinder: 2 mm
Bottom: 2 mm
Internal diameter tank: 1.150 mm
Outer diameter tank: 1.250 mm

Cylinder height: 1.000 mm
Total height of tank: 1.900 mm
Empty weight tank: 700

SKU: 451367

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 90 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Dobbeltmantelen må drives uten trykk; 2 elektriske varmeovner (6 kW) for oppvarming av varmemediet i dobbeltmantelen; OBS: Tanken leveres uten varmemedium (glyserin)
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 1 000 mm
Innvendig diameter: 1 150 mm
Total høyde: 1 900 mm
Ytre diameter: 1250 mm

Omrører

Effekt (kW): 0,75
Turtall: 0 – 1400

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter

Mer

Isolert: Ja
Vekt: 700

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se