1000 liters tank i syrefast 316

302 000 SEK /st exkl moms

Additional information: Apparatus was manufactured for a global pharmaceutical company but never put into operation there; hand hole with sight glass diameter: 285mm; incl. Südmo single seat valve SVP (outlet)
Volumetric volume (L): 1.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 60 L
Max Overpressure: 10 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Top: 4,50 mm
Cylinder: 6 mm

Bottom: 4 mm
Internal diameter tank: 1.000 mm
Outer diameter tank: 1.194 mm
Cylinder height: 1.332 mm
Empty weight tank: 800

SKU: 447773

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Tanken ble produsert for et globalt farmasøytisk selskap, men ble aldri tatt i bruk; håndhull med skueglass diameter: 285 mm; inkl. Südmo enkeltseteventil SVP (utløp); vi kan ikke oppgi noen
Øvrig informasjon2: garantier om varme-/kjølekappen
Omrører: Nei
Overtrykk: 6 barer
Total uttapping:
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 1332 mm
Innvendig diameter: 1 000 mm
Ytre diameter: 1,194 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 6 millimeter
Topp: 4,50 mm

Mer

Isolert: Ja
Vekt: 800

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor