

1000 liters tank i syrefast 316



64 000 SEK /st exkl moms

item available on order

Article type: second-hand storage tank - type K-HL

Additional information: Never been used

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger



Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the middle part of the cilinder

Number of windings: 4

Height HE: 860 mm

Number of sections: 1

Water pressure HE: 2,50 Bar

Steam pressure HE: 1 Bar

Contact surface cylinder: 1,30 m²

Connection HE: 1" BSP

Working temperature HE cylinder: 100 °C

Type HE: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Manway(s): RVS 316

Gasket manway(s): parra rubber

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm



Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Internal diameter tank: 908 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 978 mm

Cylinder height: 1.500 mm

Feet height: 472 mm

Total height of tank: 2.250 mm

Empty weight tank: 135

SKU: 435602

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: enkeltmantlet med varmeveksler
Maksimal tetthet for produktet: 1200
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Aldri blitt brukt
Omrører: Nei
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk 15 °.
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1000

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 1 500 mm
Høyde på ben: 472 mm
Innvendig diameter: 908 mm
Mål utløp til bakken: 300 mm
Total høyde: 2 250 mm
Ytre diameter: 978 mm

Varmevekslere

Damptrykk varmeveksler: 1 bar
Tilkobling varmeveksler: 1" BSP
Arbeidstemperatur varmeveksler sylinder: 100 °C
Høyde varmeveksler: 860 mm
Kontaktflate sylinder: 1,30 m²
Posisjon varmeveksler: den midtre delen av cilinderen
Type varmeveksler på sylinder: halvrør sveiset på utsiden av innertanken
Vanndrykk varmeveksler: 2,50 bar

Tanktykkelse

Bunn: 2,50 mm
Sylinder: 2 millimeter
Topp: 2,50 mm

Mer

Varmeveksler: RVS 304
Isolert: Nei
Vekt: 135