

1000 liters tank i syrefast 316



214 000 SEK /st exkl moms

Additional information: Double jacket must be operated without pressure; 2 electric heaters (6 kW) for heating the heating medium in the double jacket; Attention: The vessel is delivered without heating medium (glycerine or thermal oil), which must be filled in on site before commissioning; switch cabinet for the electric heaters available (temperature of the double jacket can be regulated via switch cabinet); 2 ball valves for the heating jacket are included in the scope of delivery; contrary to the information in the drawing, the inside of



the vessel is not polished

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0 - 1400

Power: 0,75

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 1.150 mm

Outer diameter tank: 1.250 mm

Cylinder height: 1.000 mm

Total height of tank: 1.900 mm

Empty weight tank: 700

SKU: 415205



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 90 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Dobbeltmantelen må drives uten trykk; 2 elektriske varmeovner (6 kW) for oppvarming av varmemediet i dobbeltmantelen; OBS: Tanken leveres uten varmemedium (glyserin)

Øvrig informasjon2:

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 1000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1 000 mm
Innvendig diameter: 1 150 mm
Total høyde: 1 900 mm
Ytre diameter: 1250 mm

Omrører

Effekt (kW): 0,75
Turtall: 0 – 1400

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter

Mer

Isolert: Ja
Vekt: 700