1000 liters tank i syrefast 316

71 000 SEK /st exkl moms

Additional information: 1 Screw connection of the manhole cover damaged
Volumetric volume (L): 1.000 L
Pressure in tank: pressure
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 2 Bar

Max. temperature (°C): 120 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 97 L
Max Overpressure: 2 Bar

Max. working temperature: 134 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Internal diameter tank: 1.180 mm

Outer diameter tank: 1.360 mm
Total height of tank: 1.950 mm

SKU: 486017

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 120 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; 1 skrueforbindelse på kumlokket er skadet; vi kan ikke gi noen garantier for varme-/kjølekappen
Omrører: Nei
Overtrykk: 2 barer
Total uttapping: Ja
Undertrykk (vakuum):
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Innvendig diameter: 1 180 mm
Total høyde: 1 950 mm
Ytre diameter: 1 360 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor