10000 liters tank i syrefast 316

173 000 SEK /st exkl moms

Additional information: Slurry; Type plate no longer available; Diameter manhole cylinder 600 mm; 2 more identical containers are available on request; some residues of previous content
Volumetric volume (L): 10.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Outlet of tank: flange DN80
Agitator: yes
Power: 3
Cylinder: 3 mm
Bottom: 4 mm

Internal diameter tank: 2.500 mm
Cylinder height: 2.000 mm
Total height of tank: 3.800 mm
Empty weight tank: 1.500

SKU: 438830

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 80 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon:
Øvrig informasjon2: omrøreren
Omrører: Ja
Total uttapping: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 10000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 2 000 mm
Innvendig diameter: 2 500 mm
Total høyde: 3 800 mm

Omrører

Effekt (kW): 3

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tanktykkelse
Bunn: 4 mm
Sylinder: 3 mm

Mer
Isolert: Nei
Vekt: 1.500