

10450 liters tank i syrefast 316



219 000 SEK /st exkl moms

Volumetric volume (L): 10.450 L

Pressure in tank: pressure

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 34 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN80 DIN 11851

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 2.450 mm

Cylinder height: 2.000 mm

Total height of tank: 3.150 mm

Empty weight tank: 1.200

SKU: 422855

Mer information



Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 120 °C

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 10450

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Ja

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 2 000 mm

Innvendig diameter: 2450 mm

Total høyde: 3 150 mm

Tanktykkelse

Bunn: 3 mm

Sylinder: 3 mm



Mer

Isolert: Nei

Vekt: 1.200