

1050 liters tank i syrefast 316



75 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type BBT-ES-SL

Volumetric volume (L): 1.050 L

Max. density P (kg/m³): 1.200

Finish stainless steel: pickled

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 316

Gasket manway(s): EPDM

Valve: RVS 316L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no



Tank outlet: inside Ø 50 mm

Outlet type: DIN11851 male

Total outlet valve: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 200 mm

Outer diameter tank: 1.140 mm

Cylinder height: 720 mm

Total height of tank: 1.573 mm

Empty weight tank: 130

SKU: 378362

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: trykk
Finish rustfritt stål: pickled
Konfiguration: enkelthudet
Maksimal tetthet for produktet: 1200
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Overtrykk: 2 barer
Tankens form: sylindrisk
Total uttapping:
Type bunn: tallerken
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 1050

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Med inspeksjon utført av: TUV
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann
Utløpsventil: Ja

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L



Tankdimensjoner

Sylinderhøyde: 720 mm
Mål utløp til bakken: 200 mm
Total høyde: 1,573 mm
Ytre diameter: 1140 mm

Tanktykkelse

Bunn: 2,50 mm
Sylinder: 2 millimeter
Topp: 2,50 mm

Mer

Isolert: Nei
Vekt: 130