

1085 liters tank i syrefast 316



101 000 SEK /st exkl moms

Additional information: Biochemistry; Welded stainless steel ring around the outside of the vessel (protrudes approx. 100 mm from the outer diameter (insulation)); some residues of previous content

Volumetric volume (L): 1.085 L

Pressure in tank: pressure

Max. temperature (°C): 95 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 17 L

Max Overpressure: 3,50 Bar

Max. working temperature: 143 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 48

Agitator: yes

Power: 1,10

Internal diameter tank: 990 mm

Outer diameter tank: 1.130 mm

Cylinder height: 1.240 mm

Total height of tank: 2.150 mm

SKU: 564685



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 95 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 1085

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 1 240 mm

Innvendig diameter: 990 mm

Total høyde: 2 150 mm

Ytre diameter: 1 130 mm



Omrører

Effekt (kW): 1,10

Mer

Isolert: Ja