

1 100 liters tank i syrefast 316



30 000 SEK /st exkl moms

Article type: second-hand transport tank

Additional information: Previous product was Methyl Acrylate (Cas. No. 96-33-3), the tanks are empty and cleaned; the tanks have not been used much and are in very good condition; UN marking.

Volumetric volume (L): 1.100 L

Pressure in tank: pressure

Max. pressure (Bar): 0,30 Bar

Min. pressure (Bar): 0,05 Bar

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: flat sloping

Total discharge: yes

Fixation points: 4 stackable frame

Manway(s): RVS 316

Gasket manway(s): PTFE

Valve: RVS 316L

Gasket shut-off valve (mat): PTFE

Fixation point(s): galvanised steel

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 50 mm

Total outlet valve: yes

Top: 1,70 mm

Cylinder: 1,70 mm

Bottom: 1,70 mm

Distance from outlet to ground: 229 mm

Outer diameter tank: 1.070 mm

Cylinder height: 1.065 mm

Total height of tank: 1.798 mm

Total outer width: 1.100 mm

Total outer length: 1.200 mm



Empty weight tank: 280

SKU: 567800

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Tidligere produkt var Metylakrylat (Cas. No. 96-33-3), tankene er tomme og rengjorte; tankene har ikke vært mye brukt og er i svært god stand; UN-merking.

Omrører: Nei

Overtrykk: 0,30 bar

Tankens form: sylindrisk

Total uttapping:

Type bunn: flat skråning

Undertrykk (vakuum): 0,05 bar

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316L (V4A)

Volum i liter: 1100



Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Tankutløp: innvendig Ø 50 mm

Teknisk tegning finnes: Ja

Utløpsventil: Ja

Materialoversikt

Materiale: Syrefast 316

Festepunkt(er): galvanisert stål

Tankdimensjoner

Sylinderhøyde: 1 065 mm

Mål utløp til bakken: 229 mm

Total høyde: 1 798 mm

Ytre diameter: 1 070 mm

Tanktykkelse

Bunn: 1,70 mm

Sylinder: 1,70 mm

Topp: 1,70 mm

Mer

Isolert: Nei

Vekt: 280