

## 1150 liters tank i rustfritt stål 304



136 000 SEK /st exkl moms

**Volumetric volume (L):** 1.150 L

**Pressure in tank:** ATM - atmospheric

**Max. temperature (°C):** 80 °C

**Material wet parts:** SS AISI 304 (V2A)



**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 0 - 10

**Power:** 1,50

**Internal diameter tank:** 1.200 mm

**Cylinder height:** 938 mm

**Total height of tank:** 1.850 mm

**Empty weight tank:** 270

**SKU:** 567755

## Mer information



## Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Nyprodusert

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 80 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 1150

## Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

## Materialoversikt

Materiale: Rustfritt stål 304

## Tankdimensjoner

Sylinderhøyde: 938 mm

Innvendig diameter: 1 200 mm

Total høyde: 1 850 mm

## Omrører

Effekt (kW): 1,50

Turtall: 0 – 10



## Mer

Isolert: Nei

Vekt: 270