

11700 liters tank i syrefast 316



227 000 SEK /st exkl moms

Additional information: dairy; double jacket probably with drip ring - suitable only for cooling

Volumetric volume (L): 11.700 L

Pressure in tank: pressure

Max. pressure (Bar): 0,99 Bar



Max. temperature (°C): 99 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 0,99 Bar

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 12 / 25

Power: 1.2 / 2.2

Internal diameter tank: 3.140 mm

Outer diameter tank: 3.250 mm

Cylinder height: 1.180 mm

Total height of tank: 4.650 mm

SKU: 391457



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 99 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: meieri; dobbel kappe sannsynligvis med dryppring – kun egnet for kjøling; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 0,99 bar

Total uttapping: Ja

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 11700

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 1 180 mm

Innvendig diameter: 3140 mm

Total høyde: 4 650 mm

Ytre diameter: 3 250 mm



Omrører

Effekt (kW): 1.2 / 2.2

Turtall: 12 / 25

Mer

Isolert: Nei