12000 liters tank i rustfritt stål 304

113 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 12.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: cylinder
Height manhole 1 (mm): 435 mm x H 315 mm
Tank outlet: inside Ø 40 mm

Outlet type: DIN11851 female
Agitator: yes
Agitator type: propeller agitator
Position engine: in the cylinder
Number of revolutions: 700

Power: 1,10
Voltage: three-phase
Insulation top: yes
Insulation body: yes
Insulation bottom/sides: yes

finish of the outer jacket: welded
Insulation thickness: 50
Internal diameter tank: 2.400 mm
Distance from outlet to ground: 400 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Outer diameter tank: 2.500 mm

Cylinder height: 2.700 mm
Total height of tank: 4.100 mm
Empty weight tank: 1.500

SKU: 384839

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 12000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 40 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpstype: DIN11851 hunn

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Isolasjonsmateriale: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Utvendig kledning: RVS 304

Tankdimensjoner

Sylinderhøyde: 2700 mm
Innvendig diameter: 2 400 mm
Mål utløp til bakken: 400 mm
Total høyde: 4 100 mm
Ytre diameter: 2 500 mm

Omrører

Effekt (kW): 1,10
Motorposisjon: i sylinderen
Type omrører: propellomrører
Turtall: 700
Spenning (Volt): trefaset

Tykkelse på ytterbekledning og isolasjon

Finish utvendig kappe: sveiset
Isolasjon bunn/gavler: Ja
Isolasjon kappe: Ja
Isolasjonsmateriale: Rockwool

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer

Isolasjonsmateriale: Ja
Isolasjonstykkelse OW: 50
Isolert: Ja
Vekt: 1.500

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se