# 1229 liter tank i syrefast 316

222 000 SEK /st exkl moms

**Additional information**: Tank was rebuilt in 2011; further technical documents available
**Volumetric volume (L)**: 1.229 L
**Pressure in tank**: pressure and vacuum
**Max. pressure (Bar)**: 3 Bar

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Min. pressure (Bar)**: 1 Bar

**Max. temperature (°C)**: 150 °C
**Material wet parts**: SS AISI 316 (V4A)
**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no

**Insulation**: yes
**Mobile tank**: no
**Total discharge**: yes
**Volume**: 88 L
**Max Overpressure**: 3 Bar

**Max. working temperature**: 150 °C
**Type HE on the bottom**: heating/cooling jacket
**Type HE on the cylinder**: heating/cooling jacket
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: yes
**Flange for agitator**: no
**Position of manway**: headside
**Outlet of tank**: 30
**Top**: 6,50 mm

**Cylinder**: 8 mm
**Bottom**: 5,70 mm
**Internal diameter tank**: 1.188 mm
**Outer diameter tank**: 1.347 mm
**Cylinder height**: 750 mm

**Total height of tank**: 2.350 mm

**SKU:** 417212



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

# Mer information

## Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; Tanken ble bygget om i 2011; ytterligere tekniske dokumenter er tilgjengelige; vi kan ikke gi noen garantier om varme-/kjølekappen
Omrører: Nei
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1229

## Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

## Materialoversikt

Materiale: Syrefast 316



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Tankdimensjoner**

Sylinderhøyde: 750 mm
Innvendig diameter: 1,188 mm
Total høyde: 2350 mm
Ytre diameter: 1347 mm

**Tanktykkelse**

Bunn: 5,70 mm
Sylinder: 8 millimeter
Topp: 6,50 mm

**Mer**

Isolert: Ja

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor