124 liters tank i syrefast 316

51 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe inside the tank (see pictures); GEMÜ bottom outlet diaphragm valve at the outlet. Technical documentation available from the manufacturer.
Volumetric volume (L): 124 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 14 L
Max Overpressure: 2 Bar

Max onderdruk: 1 Bar
Max. working temperature: 50 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: clamp

Internal diameter tank: 500 mm
Cylinder height: 680 mm
Total height of tank: 1.250 mm

SKU: 481714

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: apotek; påfyllingsrør inne i tanken (se bilder); GEMÜ membranventil i bunnutløpet ved utløpet. Teknisk dokumentasjon tilgjengelig fra produsenten; vi kan ikke gi noen garantier om
Øvrig informasjon2: varme-/kjølekappen
Omrører: Nei
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 124

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 680 mm
Innvendig diameter: 500 mm
Total høyde: 1250 mm

Mer

Varmeveksler: RVS 304
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor