12600 liters tank i syrefast 316

176 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K3-SL
Volumetric volume (L): 12.600 L
Max. density P (kg/m³): 1.200
Ra inner weld: 1,60
Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: conical 15 °

Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 4 adjustable feet
Manway(s): RVS 316

Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Inspection of: TUV
Flange for agitator: no
Number of manways: 1
Height manhole 1 (mm): 500 mm

CIP spray ball: no, optional
Tank outlet: inside Ø 65 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional
Agitator: no, optional

Top: 2 mm
Cylinder: 2 mm
Bottom: 2 mm
Distance from outlet to ground: 306 mm
Outer diameter tank: 2.150 mm

Cylinder height: 3.250 mm
Feet height: 710 mm
Total height of tank: 4.324 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Empty weight tank: 534

SKU: 380060

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: ATM – atmosfærisk
Finish rustfritt stål: 2b
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 80 °C
Maksimal tetthet for produktet: 1200
Min. arbeidstemperatur: -10 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Ra innvendig sveis: 1,60
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk 15 °.
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 12600

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Med inspeksjon utført av: TUV
Tankutløp: innvendig Ø 65 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L

Tankdimensjoner

Sylinderhøyde: 3 250 mm
Høyde på ben: 710 mm
Mål utløp til bakken: 306 mm
Total høyde: 4 324 mm
Ytre diameter: 2 150 mm

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter
Topp: 2 millimeter

Mer

Isolert: Nei
Vekt: 534

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor