

1300 liters tank i rustfritt stål 304



88 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank

Volumetric volume (L): 1.300 L

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): -0,15 Bar

Max. temperature (°C): 130 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical



Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 non adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Water pressure HE: 5,20 Bar

Working temperature HE cylinder: 80 °C

Type of HE on the bottom: dimple-jacket

Heat exchanger bottom connected with cylinder: yes

Water pressure HE: 5,20 Bar

Working temperature HE bottom: 80 °C

Heat exchanger: RVS 304

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 304L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: headside

CIP spray ball: no, optional

Tank outlet: inside Ø 32 mm

Outlet type: DN32

Total outlet valve: yes

Agitator: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 3 mm

Distance from outlet to ground: 326 mm

Outer diameter tank: 1.140 mm

Cylinder height: 935 mm

Total height of tank: 2.018 mm

Empty weight tank: 179

SKU: 450488

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: trykk
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 130 °C
Min. arbeidstemperatur: -10 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Overtrykk: 2 barer
Tankens form: sylindrisk
Total uttapping:
Type bunn: sterk konisk
Undertrykk (vakuum): -0,15 Bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 1300

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 32 mm
Teknisk tegning finnes: Ja
Utløpstype: DN32
Utløpsventil: Ja

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 935 mm
Mål utløp til bakken: 326 mm
Total høyde: 2,018 mm
Ytre diameter: 1140 mm

Varmevekslere

Arbeidstemperatur varmeveksler sylinder: 80 °C
Arbeidstemperatur varmeveksler bunn: 80 °C
Posisjon varmeveksler: den komplette sylinderen
Type varmeveksler på sylinder: dimple jakke
Type varmeveksler på bunn: dimple jakke
Vanntrykk varmeveksler: 5,20 bar
Vanntrykk varmeveksler bunn: 5,20 bar

Tanktykkelse

Bunn: 3 mm
Sylinder: 2 millimeter
Topp: 2 millimeter

Mer

Varmeveksler: RVS 304
Isolert: Nei
Vekt: 179