1300 liters tank i syrefast 316

187 000 SEK /st exkl moms

Additional information: Pharmacy; Various technical documents available
Volumetric volume (L): 1.300 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 80 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 140 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 50

Agitator: yes
Number of revolutions: 417
Power: 1,10
Top: 4,50 mm
Cylinder: 5,70 mm

Bottom: 7,50 mm
Internal diameter tank: 1.200 mm
Outer diameter tank: 1.470 mm
Cylinder height: 830 mm
Total height of tank: 2.100 mm

SKU: 443318

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 130 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; Ulike tekniske dokumenter tilgjengelig; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1300

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner

Sylinderhøyde: 830 mm
Innvendig diameter: 1 200 mm
Total høyde: 2100 mm
Ytre diameter: 1 470 mm

Omrører

Effekt (kW): 1,10
Turtall: 417

Tanktykkelse

Bunn: 7,50 mm
Sylinder: 5,70 mm
Topp: 4,50 mm

Mer

Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor