1345 liters tank i syrefast 316

89 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 2 claws made of stainless steel 304 (contact surface the other way round; see photos); flanges partly made of Fe; further technical documents available; bump at the insulation jacket
Volumetric volume (L): 1.345 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 24 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Top: 5 mm
Cylinder: 5 mm

Bottom: 4 mm
Internal diameter tank: 1.000 mm
Outer diameter tank: 1.250 mm
Cylinder height: 1.360 mm
Total height of tank: 2.350 mm

SKU: 397550

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; 2 støttebraketter laget av Aisi 304 (kontaktflate den andre veien rundt; se bilder); flenser delvis laget av Fe; ytterligere tekn. dokumenter tilgjengelig; bump på
Øvrig informasjon2: isolasjonsjakke; vi kan ikke gi noen garantier for varme-/kjølekappen
Omrører: Nei
Overtrykk: 3,20 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1345

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner

Sylinderhøyde: 1 360 mm
Innvendig diameter: 1 000 mm
Total høyde: 2350 mm
Ytre diameter: 1250 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 5 mm
Topp: 5 mm

Mer

Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se