

1410 liters tank i syrefast 316



192 000 SEK /st exkl moms

Additional information: 4 stainless steel claws; total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; 1 dirt protection collar on the outside above the claws (diameter approx. 1,740 mm)

Volumetric volume (L): 1.410 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 93 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 65

Agitator: yes

Number of revolutions: 960

Power: 3

Top: 6,10 mm

Cylinder: 8,40 mm

Bottom: 6,90 mm

Internal diameter tank: 1.300 mm

Outer diameter tank: 1.450 mm

Cylinder height: 700 mm

Total height of tank: 2.250 mm



SKU: 434294

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: isolert med varmeveksler

Maks. arbeidstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Kosmetikk; 4 støttebraketter, rustfritt stål; Total høyde er estimert; 1 varmekobling avskåret; lett metallisk misfarging inne i tanken; 1 smussbeskyttelseskrage på utsiden over

Øvrig informasjon2: støttebrakettene (diameter ca. 1740 mm); vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for røreverket

Omrører: Ja

Overtrykk: 3 barer

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 1410



Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 700 mm
Innvendig diameter: 1 300 mm
Total høyde: 2 250 mm
Ytre diameter: 1 450 mm

Omrører

Effekt (kW): 3
Turtall: 960

Tanktykkelse

Bunn: 6,90 mm
Sylinder: 8,40 mm
Topp: 6,10 mm

Mer

Isolert: Ja