1490 liters tank i syrefast 316

114 000 SEK /st exkl moms

Additional information: food; 1 dent in the insulation jacket; manhole diameter 450 mm; some residues of previous content; manhole cover is missing; motor-/gear is missing
Volumetric volume (L): 1.490 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 65 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 130 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: 35
Agitator: yes
Internal diameter tank: 1.190 mm
Outer diameter tank: 1.350 mm
Cylinder height: 1.000 mm

Total height of tank: 2.750 mm

SKU: 390515

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 130 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: mat; 1 bulk i isolasjonsmantelen; kumdiameter 450 mm; noen rester av tidligere innhold; kumlokk mangler; motor-/gear mangler; vi kan ikke gi noen garantier om
Øvrig informasjon2: varme-/kjølekappe; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 2 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1490

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner

Sylinderhøyde: 1 000 mm
Innvendig diameter: 1190 mm
Total høyde: 2750 mm
Ytre diameter: 1350 mm

Mer

Varmeveksler: RVS 304
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor