

150 liters tank i syrefast 316



96 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: The tank has never been used

Volumetric volume (L): 150 L

Max. density P (kg/m³): 1.400

Ra inner weld: 1,60

Pressure in tank: vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 150 °C

Min. temperature (°C): -10 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: flat

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 non adjustable feet

Gasket manway(s): PTFE

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 461 mm

Tank outlet: inside Ø 76 mm

Outlet type: DN65 EN1092-1

Agitator: no

Top: 36 mm

Cylinder: 3 mm

Bottom: 4 mm

Tank capacity top cylinder: 150 L

Internal diameter tank: 461,60 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 615 mm

Cylinder height: 856 mm

Total height of tank: 1.414 mm



Empty weight tank: 300

SKU: 387362

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: vakuum

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 150 °C

Maksimal tetthet for produktet: 1400

Min. arbeidstemperatur: -10 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: tanken har aldri vært brukt

Omrører: Nei

Overtrykk: 6 barer

Ra innvendig sveis: 1,60

Tankens form: sylindrisk

Total uttapping:

Type bunn: tallerken

Undertrykk (vakuum): -1 bar

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 150



Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 76 mm
Teknisk tegning finnes: Ja
Utløpstype: DN65 EN1092-1

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L

Tankdimensjoner

Sylinderhøyde: 856 mm
Innvendig diameter: 461,60 mm
Mål utløp til bakken: 250 mm
Total høyde: 1,414 mm
Ytre diameter: 615 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 3 mm
Topp: 36 mm

Mer

Isolert: Nei
Vekt: 300