1500 liters tank i syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

133 000 SEK /st exkl moms

Additional information: chemistry; some residues of previous content
Volumetric volume (L): 1.500 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 360 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: 20
Cylinder: 8 mm
Bottom: 7 mm
Internal diameter tank: 1.250 mm
Outer diameter tank: 1.450 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Empty weight tank: 1.500

SKU: 409550

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: kjemi; noen rester av tidligere innhold; vi kan ikke gi noen garantier om varme-/kjølekappen
Omrører: Nei
Overtrykk: 3,20 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1500

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Materialoversikt
Materiale: Syrefast 316

Tankdimensjoner
Innvendig diameter: 1250 mm
Ytre diameter: 1 450 mm

Tanktykkelse
Bunn: 7 millimeter
Sylinder: 8 millimeter

Mer
Varmeveksler: RVS 304
Isolert: Ja
Vekt: 1.500

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor