15000 liters tank i rustfritt stål 304

144 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 15.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet

Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: no
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: headside

Hinged lid: yes
Tank outlet: inside Ø 60 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top

Number of revolutions: 25
Power: 4
Voltage: 380 V - three-phase
Distance from outlet to ground: 120 mm
Outer diameter tank: 2.300 mm

Cylinder height: 2.700 mm
Total height of tank: 4.350 mm
Empty weight tank: 900

SKU: 485924

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: tallerken
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 15000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Tankutløp: innvendig Ø 60 mm
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 2700 mm
Mål utløp til bakken: 120 mm
Total høyde: 4 350 mm
Ytre diameter: 2 300 mm

Omrører

Effekt (kW): 4
Motorposisjon: på toppen
Type omrører: propellomrører
Turtall: 25
Spenning (Volt): 380 V – trefase

Mer

Isolert: Nei
Vekt: 900

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se