

15000 liter tank i rustfritt stål 304 (dobbeltmantlet)



192 000 SEK /st exkl moms

Additional information: Safety double jacket made of stainless steel 304 around the vessel; various technical documents (in French and English); manhole DN 500 with dip pipes; tanks with (sometimes stronger) dents in the double jacket (in one tank also in the inner tank; see photos); connections for safety



double jacket waved off.

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: non-existent

Cylinder: 6 mm

Bottom: 5,30 mm

Internal diameter tank: 2.200 mm

Outer diameter tank: 2.350 mm

Total outer length: 4.460 mm

SKU: 458636

Mer information



Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Horisontal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: 1 tank også i innertanken; se bilder); Tilkoblinger for sikkerhetsjakke kuttet av

Omrører: Nei

Total uttapping: Nei, det er det ikke.

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 15000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Innvendig diameter: 2 200 mm

Ytre diameter: 2350 mm

Tanktykkelse

Bunn: 5,30 mm

Sylinder: 6 millimeter



Mer

Isolert: Nei