

1600 liters tank i syrefast 316



62 000 SEK /st exkl moms

Additional information: 2 loose bearing shells made of stainless steel 304; DN 500 manhole; the exterior of the tank was sandblasted; 1 dent in the cylinder

Volumetric volume (L): 1.600 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)



Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Cylinder: 5 mm

Bottom: 3,90 mm

Internal diameter tank: 990 mm

Total height of tank: 1.700 mm

Total outer length: 2.550 mm

SKU: 483326

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Horisontal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: 2 løse lagerskall, Aisi 304; mannhull DN 500

Omrører: Nei

Total uttapping: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 1600

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Nei, det er det ikke.

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Innvendig diameter: 990 mm

Total høyde: 1 700 mm

Tanktykkelse

Bunn: 3,90 mm

Sylinder: 5 mm

Mer

Isolert: Nei

