



16000 liters tank i syrefast 316



266 000 SEK /st exkl moms

Additional information: Chemistry; Suspended design on 4 feet, Fe (Caution: heating connections extend beyond the foot ends; foot ends were screwed to a working platform); manhole cover is missing

Volumetric volume (L): 16.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 490 L

Max Overpressure: 16 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 180

Agitator: yes

Number of revolutions: 30 / 46

Power: 15

Internal diameter tank: 2.800 mm

Cylinder height: 2.650 mm

Total height of tank: 5.350 mm

SKU: 419735

Mer information



Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 200 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Kjemi; Opphengt design på 4 fot, Fe (Forsiktig: varmeforbindelser strekker seg utover fotendene; fotendene ble skrudd fast til en arbeidsplattform); kumlukk mangler; vi kan ikke gi noen

Øvrig informasjon2: garantier om omrøreren

Omrører: Ja

Overtrykk: 2 barer

Total uttapping:

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 16000

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 2650 mm

Innvendig diameter: 2 800 mm

Total høyde: 5 350 mm



Omrører

Effekt (kW): 15

Turtall: 30 / 46

Mer

Isolert: Nei