

185 liters tank i syrefast 316



121 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information:

The tanks have never been used.

Volumetric volume (L): 185 L

Pressure in tank: pressure

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 130 °C



Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: flat

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 non adjustable feet

Gasket manway(s): PTFE

Fixation point(s): RVS 316

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: outside Ø 65 mm

Agitator: no

Top: 38 mm

Cylinder: 4 mm

Bottom: 4 mm

Internal diameter tank: 502 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 670 mm

Total height of tank: 1.440 mm

Total outer width: 755,50 mm

Total outer length: 751,50 mm



Empty weight tank: 200

SKU: 439217

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkelthudet

Maks. arbeidstemperatur: 130 °C

Min. arbeidstemperatur: -10 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Tankene har aldri vært i bruk.

Omrører: Nei

Overtrykk: 6 barer

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: tallerken

Undertrykk (vakuum): -1 bar

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316L (V4A)

Volum i liter: 185



Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Tankutløp: utvendig Ø 65 mm
Teknisk tegning finnes: Ja

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 316

Tankdimensjoner

Innvendig diameter: 502 mm
Mål utløp til bakken: 250 mm
Total høyde: 1 440 mm
Ytre diameter: 670 mm

Tanktykkelse

Bunn: 4 mm
Sylinder: 4 mm
Topp: 38 mm

Mer

Isolert: Nei
Vekt: 200