1969 liters tank i syrefast 316

119 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 2 stainless steel 304 claws (contact surface the other way round; see photos); some residues of previous content
Volumetric volume (L): 1.969 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 70 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 571

Power: 1,10
Cylinder: 6 mm
Bottom: 5,70 mm
Internal diameter tank: 1.000 mm
Cylinder height: 2.110 mm

Total height of tank: 3.800 mm

SKU: 410366

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; 2 støttebraketter laget av Aisi 304 (kontaktflate motsatt vei; se bilder); noen rester av tidligere innhold; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 3,20 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 1969

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Sylinderhøyde: 2,110 mm
Innvendig diameter: 1 000 mm
Total høyde: 3 800 mm

Omrører
Effekt (kW): 1,10
Turtall: 571

Tanktykkelse
Bunn: 5,70 mm
Sylinder: 6 millimeter

Mer
Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor