

200 liters tank i syrefast 316



65 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type CBS-HLA

Additional information: flange for agitator is forseen; *article price without agitator*; feel free to ask for agitation possibilities on this tank; $Ra < 0.8 \mu m$

Volumetric volume (L): 200 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic



Max. temperature (°C): 80 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Type of HE on the cylinder: dimple-jacket

Height HE: 375 mm

Number of sections: 1

Water pressure HE: 3 Bar

Contact surface cylinder: 0,33 m²

Connection HE: 1"bsp male

Working temperature HE cylinder: 80 °C

Heat exchanger: RVS 304

Manway(s): RVS 316

Gasket manway(s): EPDM

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 690 mm

Cylinder height: 500 mm

Total height of tank: 1,122 mm

Empty weight tank: 120

SKU: 378020

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Nyprodusert

Arbeidstrykk i tank:

Finish rustfritt stål: 2b

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 80 °C

Maksimal tetthet for produktet: 1200

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: flens for omrører er forutsett; artikkelpris uten omrører; spør gjerne om omrøringsmuligheter på denne tanken; Ra=<0,8µm

Omrører: Nei

Ra innvendig sveis: 0,80

Tankens form: sylindrisk

Total uttapping:

Type bunn: konisk 15 °.

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316L (V4A)

Volum i liter: 200

Utstyr

Flens for omrører: Ja

Merkeskilt: Ja

Næringsmiddelgodkjent: Ja

Tankutløp: innvendig Ø 40 mm

Teknisk tegning finnes: Ja

Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Syrefast 316

Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 500 mm
Mål utløp til bakken: 250 mm
Total høyde: 1,122 mm
Ytre diameter: 690 mm

Varmevekslere

Tilkobling varmeveksler: 1" BSP hann
Arbeidstemperatur varmeveksler sylinder: 80 °C
Høyde varmeveksler: 375 mm
Kontaktflate sylinder: 0,33 m²
Type varmeveksler på sylinder: dimple jakke
Vanntrykk varmeveksler: 3 barer

Tanktykkelse

Bunn: 3 mm
Sylinder: 3 mm
Topp: 3 mm

Mer

Varmeveksler: RVS 304
Isolert: Nei
Vekt: 120