

200 liters tank i syrefast 316



36 000 SEK /st exkl moms

Additional information: Vessel hangs in former stainless steel tilting frame (currently cannot be tilted); vessel open at the top with screwed, hinged stainless steel protective grille; outlet with plunger (would have to be reworked on site; plunger does not close tightly)

Volumetric volume (L): 200 L

Pressure in tank: pressure



Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: open
Total discharge: yes
Volume: 35 L
Max Overpressure: 4 Bar
Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 1.450
Power: 2,20

Internal diameter tank: 740 mm
Outer diameter tank: 780 mm
Total height of tank: 1.850 mm

SKU: 483860



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 100 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon:

Øvrig informasjon2: modifisering på stedet; stampelet lukker ikke tett); vi kan ikke gi noen garantier om omrøreren

Omrører: Ja

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 200

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Innvendig diameter: 740 mm

Total høyde: 1 850 mm

Ytre diameter: 780 mm



Omrører

Effekt (kW): 2,20

Turtall: 1.450

Mer

Isolert: Nei