2000 liters tank i syrefast 316

204 000 SEK /st exkl moms

Additional information: Manhole approx. 308 x 440 mm; Total height as per drawing
Volumetric volume (L): 2.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 15 L
Max Overpressure: 3 Bar
Max. working temperature: 90 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: yes
Position of manway: in the bottom
Outlet of tank: 50

Internal diameter tank: 1.050 mm
Outer diameter tank: 1.150 mm
Cylinder height: 2.500 mm
Total height of tank: 3.700 mm

SKU: 463155

Mer information

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 90 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Mannhull ca. 308 x 440 mm; Total høyde i henhold til tegning; vi kan ikke gi noen garantier for varme-/kjølekappen
Omrører: Nei
Total uttapping: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 2000

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Ja
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 2 500 mm
Innvendig diameter: 1 050 mm
Total høyde: 3 700 mm
Ytre diameter: 1 150 mm

Mer

Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor