20000 liters tank i rustfritt stål 304

202 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 20.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Hinged lid: yes
Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Power: 1,20
Voltage: 400 V - three-phase
Current: 4,20
Distance from outlet to ground: 500 mm

Outer diameter tank: 3.260 mm
Cylinder height: 2.535 mm
Total height of tank: 4.450 mm
Empty weight tank: 1.950

SKU: 417479

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Konfiguration: isolert
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 20000

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 2 535 mm
Mål utløp til bakken: 500 mm
Total høyde: 4 450 mm
Ytre diameter: 3 260 mm

Omrører

Effekt (kW): 1,20
Motorposisjon: på toppen
Type omrører: propellomrører
Spenning (Volt): 400 V – trefase

Mer

Isolert: Ja
Vekt: 1.950

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor