20300 liters tank i rustfritt stål 304

196 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K3-SL
Volumetric volume (L): 20.300 L
Max. density P (kg/m³): 1.340
Ra inner weld: 1,60
Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 304L (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: conical 15 °

Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 5 adjustable feet
Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 304L
Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Inspection of: TUV
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 500 mm
Tank outlet: inside Ø 65 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional

Agitator: no, optional
Top: 2,50 mm
Cylinder: 2 mm
Bottom: 3 mm
Distance from outlet to ground: 306 mm

Outer diameter tank: 2.400 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Cylinder height: 4.250 mm
Feet height: 744 mm
Total height of tank: 5.400 mm
Empty weight tank: 852

SKU: 389537

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank: ATM – atmosfærisk
Finish rustfritt stål: 2b
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 80 °C
Maksimal tetthet for produktet: 1340
Min. arbeidstemperatur: -10 °C
Mobil tank: Nei, det er det ikke.
Omrører: Nei
Ra innvendig sveis: 1,60
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: konisk 15 °.
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304L (V2A)
Volum i liter: 20300

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Med inspeksjon utført av: TUV
Tankutløp: innvendig Ø 65 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304L

Tankdimensjoner

Sylinderhøyde: 4 250 mm
Høyde på ben: 744 mm
Mål utløp til bakken: 306 mm
Total høyde: 5 400 mm
Ytre diameter: 2 400 mm

Tanktykkelse

Bunn: 3 mm
Sylinder: 2 millimeter
Topp: 2,50 mm

Mer

Isolert: Nei
Vekt: 1.200

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor