210 liters tank i Syrefast 316

53 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: The tank has never been used, in absolute new condition, New agitator.; we can't give any guarantees about the agitator
Volumetric volume (L): 210 L
Ra inner weld: 0,80

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316L (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Shape of tank: cylindrical
Bottom type: flat
Total discharge: yes

Fixation points: 3 adjustable feet
Fixation point(s): RVS 304L
Wet parts agitator(s): SS AISI 316L (V4A)
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851

Total outlet valve: no, optional
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 1.400

Power: 0,75
Voltage: mono
Cylinder: 2 mm
Bottom: 2 mm
Internal diameter tank: 595 mm

Distance from outlet to ground: 260 mm
Outer diameter tank: 705 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Cylinder height: 770 mm
Total height of tank: 1.460 mm
Empty weight tank: 60

SKU: 383795

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: ATM – atmosfærisk
Finish rustfritt stål: 2b
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Tanken har aldri vært brukt, i absolutt ny stand, Ny røreverk; vi kan ikke gi noen garantier for røreverket
Omrører: Ja
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping: Ja
Type bunn: flat
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 210

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 40 mm
Teknisk tegning finnes: Nei, det er det ikke.
Utløpstype: DIN11851

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L
Material vätskeberörd del på omrörare: SS AISI 316L (V4A)

Tankdimensjoner

Sylinderhøyde: 770 mm
Innvendig diameter: 595 mm
Mål utløp til bakken: 260 mm
Total høyde: 1 460 mm
Ytre diameter: 705 mm

Omrører

Effekt (kW): 0,75
Motorposisjon: på toppen
Type omrører: propellomrører
Turtall: 1.400
Spenning (Volt): mono

Tanktykkelse

Bunn: 2 millimeter
Sylinder: 2 millimeter

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer

Isolert: Nei
Vekt: 60

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se