

2100 liter tank i rustfritt stål 304



180 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc T4 ; hardly ever used; we can't give any guarantees about the agitator

Volumetric volume (L): 2.100 L

Max. density P (kg/m³): 1.400

Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical



Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 supports for platform

Position HE: the complet cilinder

Water pressure HE: 2 Bar

Steam pressure HE: 0,50 Bar

Working temperature HE cylinder: 100 °C

Heat exchanger: RVS 304

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304L (V2A)

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 250

Power: 7,50

Voltage: 400 V - three-phase

Top: 5 mm

Cylinder: 7 mm

Bottom: 4 mm

Outer diameter tank: 1.560 mm

Cylinder height: 1.250 mm



Total height of tank: 1.950 mm

Empty weight tank: 960

SKU: 417893

Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 90 °C

Maksimal tetthet for produktet: 1400

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Tank AD-2000 Merkblatt, røreverk CE0344 ATEX Ex 2 1/3 G bc T4 ; nesten aldri brukt; vi kan ikke gi noen garantier for røreverket

Omrører: Ja

Overtrykk: 0,50 bar

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: tallerken

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 2100



Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Ja

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304
Material vætskeberørt del på omrørare: SS AISI 304L (V2A)

Tankdimensjoner

Sylinderhøyde: 1250 mm
Total høyde: 1 950 mm
Ytre diameter: 1560 mm

Varmevekslere

Damptrykk varmeveksler: 0,50 Bar
Arbeidstemperatur varmeveksler sylinder: 100 °C
Posisjon varmeveksler: den komplette sylinderen
Vanntrykk varmeveksler: 2 barer

Omrører

Effekt (kW): 7,50
Motorposisjon: på toppen
Type omrører: propellomrører
Turtall: 250
Spennings (Volt): 400 V – trefase

Tanktykkelse

Bunn: 4 mm
Sylinder: 7 millimeter
Topp: 5 mm



Mer

Varmeveksler: RVS 304

Isolert: Nei

Vekt: 960