2200 liter tank i rustfritt stål 304

58 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 2.200 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Hinged lid: yes
Tank outlet: inside Ø 50 mm
Agitator: yes
Position engine: in the cylinder

Position engine: at the top
Power: 0,75
Voltage: 400 V - three-phase
Current: 1,70
Distance from outlet to ground: 210 mm

Outer diameter tank: 1.800 mm
Cylinder height: 865 mm
Total height of tank: 1.900 mm

SKU: 417152

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank:
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 2200

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 50 mm
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304
Festepunkt(er): RVS 304

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tankdimensjoner

Sylinderhøyde: 865 mm
Mål utløp til bakken: 210 mm
Total høyde: 1 900 mm
Ytre diameter: 1 800 mm

Omrører

Motorposisjon: i sylinderen

Mer

Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor