

22000 liters tank i syrefast 316





227 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: There are minor differences between the tanks

Volumetric volume (L): 21.300 L

Ra inner weld: 0,80

Pressure in tank: pressure

Max. pressure (Bar): 0,49 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 4 adjustable feet

Manway(s): RVS 316

Gasket manway(s): unknown

Valve: RVS 316

Gasket shut-off valve (mat): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 445 mm x H 340 mm



Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: yes

Agitator: no, optional

Top: 4 mm

Cylinder: 2,50 mm

Bottom: 4 mm

Outer diameter tank: 2.500 mm

Cylinder height: 4.000 mm

Total height of tank: 5.900 mm

Empty weight tank: 1.000

SKU: 383870

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Det er mindre forskjeller mellom tankene

Omrører: Nei

Overtrykk: 0,49 bar

Ra innvendig sveis: 0,80

Tankens form: sylindrisk

Total uttapping: Ja

Type bunn: tallerken

Trykktank: Ja

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 21300

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Næringsmiddelgodkjent: Ja

Tankutløp: innvendig Ø 50 mm

Teknisk tegning finnes: Nei, det er det ikke.

Utløpstype: DIN11851

Utløpsventil: Ja

Materialoversikt

Materiale: Syrefast 316

Festepunkt(er): RVS 304



Tankdimensjoner

Sylinderhøyde: 4 000 mm

Total høyde: 5 900 mm

Ytre diameter: 2 500 mm

Tanktykkelse

Bunn: 4 mm

Sylinder: 2,50 mm

Topp: 4 mm

Mer

Isolert: Nei

Vekt: 1.000