

2263 liter tank i rustfritt stål 304



120 000 SEK /st exkl moms

Volumetric volume (L): 2.263 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 26 L

Max Overpressure: 2 Bar

Max. working temperature: 80 °C

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.433 mm

Outer diameter tank: 1.439 mm

Cylinder height: 1.250 mm

Total height of tank: 2.230 mm

SKU: 396740



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 80 °C

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Total uttapping: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 2263

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Ja

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 1250 mm

Innvendig diameter: 1 433 mm

Total høyde: 2 230 mm

Ytre diameter: 1,439 mm

**Tanktykkelse**

Bunn: 3 mm

Sylinder: 3 mm

Topp: 2,50 mm

Mer

Varmeveksler: RVS 304

Isolert: Nei