227 liters tank i rustfritt stål 304

246 000 SEK /st exkl moms

Additional information: pharmacy; 1 integrated control cabinet; the vessel was inspected and tested by the previous operator
Volumetric volume (L): 227 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 5 Bar

Max onderdruk: 1 Bar
Max. working temperature: 145 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 35
Agitator: yes
Power: 0,37

Cylinder: 5,60 mm
Internal diameter tank: 600 mm
Outer diameter tank: 750 mm
Cylinder height: 615 mm
Total height of tank: 1.700 mm

Total outer width: 1.050 mm
Total outer length: 1.300 mm

SKU: 488460

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 145 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: apotek; vi kan ikke gi noen garantier for varme-/kjølekappen; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 227

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Sylinderhøyde: 615 mm
Innvendig diameter: 600 mm
Total høyde: 1 700 mm
Ytre diameter: 750 mm

Omrører
Effekt (kW): 0,37

Tanktykkelse
Sylinder: 5,60 mm

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor