

2400 liters tank i syrefast 316



227 000 SEK /st exkl moms

Additional information: Pharmacy; Tank is equipped with 3 load cells (no guarantee of functionality)

Volumetric volume (L): 2.400 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 130 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 120 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 25

Agitator: yes

Number of revolutions: 263

Power: 1,50

Cylinder: 8 mm

Bottom: 7,10 mm

Internal diameter tank: 1.450 mm

Outer diameter tank: 1.506 mm

Cylinder height: 1.000 mm

Total height of tank: 2.350 mm

SKU: 409493



Mer information

Beskrivelse av produkt

Materiale: Syrefast 316

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Apotek; tanken er utstyrt med 3 veieceller (ingen garanti for funksjonalitet); vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 3 barer

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 316 (V4A)

Volum i liter: 2400

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316



Tankdimensjoner

Sylinderhøyde: 1 000 mm

Innvendig diameter: 1 450 mm

Total høyde: 2350 mm

Ytre diameter: 1506 mm

Omrører

Effekt (kW): 1,50

Turtall: 263

Tanktykkelse

Bunn: 7,10 mm

Sylinder: 8 millimeter

Mer

Isolert: Nei