2420 liters tank i syrefast 316

233 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Manhole DN 350/450 (sight glass in manhole cover missing); support ring made of Fe; flanges partly made of Fe
Volumetric volume (L): 2.420 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 100 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 130

Agitator: yes
Number of revolutions: 235
Power: 4
Top: 7 mm
Internal diameter tank: 1.400 mm

Cylinder height: 1.180 mm
Total height of tank: 3.550 mm

SKU: 413966

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkeltmantlet med varmeveksler
Maks. arbeidstemperatur: 200 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Farmasøytisk kjemi; Mannhull DN 350/450 (skueglass i mannhullsdekselet mangler); støttering, Fe; Flenser delvis laget av Fe; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 3,20 bar
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 2420

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Sylinderhøyde: 1 180 mm
Innvendig diameter: 1 400 mm
Total høyde: 3 550 mm

Omrører
Effekt (kW): 4
Turtall: 235

Tanktykkelse
Topp: 7 millimeter

Mer
Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor