

24450 liter tank i rustfritt stål 304 (dobbeltmantlet)



215 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: API650, VLAREM II, previous product Nitric acid 68%

Volumetric volume (L): 24.450 L

Max. density P (kg/m³): 1.405

Pressure in tank: ATM - atmosferic

Design pressure (Bar): 0,13 Bar

Max. temperature (°C): 50 °C



Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: double jacket for leak detection (system for detection not included)

Heat exchanger: no

Insulation: no

double jacket for leak detection (system for detection not included): yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304L

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: no

Registration plate on the tank: yes

Inspection of: VLAREM II

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Agitator: no, optional

Top: 5 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 2.800 mm

Outer diameter tank: 2.880 mm

Cylinder height: 4.000 mm

Total height of tank: 4.500 mm

Empty weight tank: 3.800

SKU: 412046



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: ATM – atmosfærisk

Designtrekk for tanken: 0,13 bar

Konfiguration: dobbel kappe for lekkasjedeteksjon (system for deteksjon ikke inkludert)

Maks. arbeidstemperatur: 50 °C

Maksimal tetthet for produktet: 1405

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: API650, VLAREM II, tidligere produkt Salpetersyre 68 %.

Omrører: Nei

Tankens form: sylindrisk

Total uttapping: Nei, det er det ikke.

Type bunn: flat

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304L (V2A)

Volum i liter: 24450

Utstyr

Flens for omrører: Nei

Merkeskilt: Ja

Med inspeksjon utført av: VLAREM II

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Utvendig kledning: RVS 304L



Tankdimensjoner

Sylinderhøyde: 4 000 mm

Innvendig diameter: 2 800 mm

Total høyde: 4500 mm

Ytre diameter: 2 880 mm

Tanktykkelse

Bunn: 5 mm

Sylinder: 5 mm

Topp: 5 mm

Mer

Isolert: Nei

Vekt: 3.800