25000 liters tank i syrefast 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

215 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: There are minor differences between the tanks
Volumetric volume (L): 25.000 L
Pressure in tank: pressure
Max. pressure (Bar): 0,49 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Top type: dished
Shape of tank: square
Bottom type: dished
Total discharge: yes

Fixation points: 6 adjustable feet
Manway(s): RVS 316
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: cylinder
Agitator: no, optional
Distance from outlet to ground: 173 mm
Outer diameter tank: 2.770 mm
Cylinder height: 4.000 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Height of top: 567 mm
Height of bottom: 567 mm
Feet height: 867 mm
Total height of tank: 5.650 mm
Empty weight tank: 1.800

SKU: 388688

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Det er mindre forskjeller mellom tankene
Omrører: Nei
Overtrykk: 0,49 bar
Tankens form: firkantet
Total uttapping: Ja
Type bunn: tallerken
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 25000

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Utstyr

Dokument finnes: Nei
Flens for omrører: Nei
Merkeskilt: Nei, det er det ikke.
Næringsmiddelgodkjent: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 4 000 mm
Høyde på ben: 867 mm
Mål utløp til bakken: 173 mm
Total høyde: 5 650 mm
Ytre diameter: 2770 mm

Mer

Isolert: Nei
Vekt: 1.800

Rodervägen 57
891 78 Bonässund
info@processoverskott.se