# 2700 liters tank i rustfritt stål 304

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

125 000 SEK /st exkl moms

**Additional information**: Manhole approx. 335 x 445 mm; CE marking and declaration of conformity only available for 2 vessels; some residues of previous content
**Volumetric volume (L)**: 2.700 L
**Pressure in tank**: pressure
**Max. pressure (Bar)**: 3 Bar
**Min. pressure (Bar)**: 3 Bar

**Material wet parts**: SS AISI 304 (V2A)
**Model**: vertical
**Configuration**: insulated
**Heat exchanger**: no
**Insulation**: yes

**Mobile tank**: no
**Total discharge**: yes
**Volume**: 10 L
**Max Overpressure**: 3 Bar
**Type HE on the bottom**: heating/cooling jacket

**Type HE on the cylinder**: heating/cooling jacket
**Documents included**: no
**Technical drawing included**: no
**Registration plate on the tank**: yes
**Flange for agitator**: no

**Position of manway**: cylinder
**Outlet of tank**: DN32 DIN 11851
**Internal diameter tank**: 1.450 mm
**Outer diameter tank**: 1.650 mm
**Cylinder height**: 1.250 mm

**Total height of tank**: 2.450 mm

**SKU:** 489772



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

## Mer information

### Beskrivelse av produkt

Materiale: Rustfritt stål 304
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk
Konfiguration: isolert med varmeveksler
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Bryggeri; Angitt total høyde i henhold til tegning; vi kan ikke gi noen garantier for varme-/kjølekappen
Øvrig informasjon2: varme-/kjølekappe
Omrører: Nei
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 3 barer
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 304 (V2A)
Volum i liter: 2700

### Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

### Materialoversikt

Materiale: Rustfritt stål 304



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Tankdimensjoner**

Sylinderhøyde: 1250 mm
Innvendig diameter: 1 450 mm
Total høyde: 2 550 mm
Ytre diameter: 1 650 mm

**Mer**

Isolert: Ja

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor