

2732 liter tank i rustfritt stål 304



64 000 SEK /st exkl moms

Additional information: chemistry; total height incl. agitator shaft; handhole diameter 200 mm; motor-/gear is missing; handhole cover is missing

Volumetric volume (L): 2.732 L

Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar



Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 51 L

Max Overpressure: 6 Bar

Max. working temperature: 80 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 25

Agitator: yes

Internal diameter tank: 1.690 mm

Cylinder height: 970 mm

Total height of tank: 2.200 mm

SKU: 393149



Mer information

Beskrivelse av produkt

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 80 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: kjemi; total høyde inkl. omrøreraksel; håndhullsdiаметer 200 mm; motor-/gear mangler; håndhullsdeksel mangler; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 0,50 bar

Total uttapping: Ja

Trykktank: Ja

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 2732

Utstyr

Dokument finnes: Nei, det er det ikke.

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Rustfritt stål 304

Tankdimensjoner

Sylinderhøyde: 970 mm

Innvendig diameter: 1690 mm

Total høyde: 2 200 mm



Mer

Varmeveksler: RVS 304

Isolert: Nei