27800 liters tank i syrefast 316

221 000 SEK /st exkl moms

Additional information: Solvents; Built according to DIN6618; indicated height is measured excluding screwed measuring devices on top of the manhole; transport dimensions are: 4,5 x 3,35 x 3,35 m
Volumetric volume (L): 27.800 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 0,10 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outer diameter tank: 3.350 mm
Total height of tank: 4.550 mm

SKU: 413366

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: enkelthudet
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Løsemidler; Bygget i henhold til DIN6618; angitt høyde er målt uten skrudd måleutstyr på toppen av mannhullet; transportdimensjoner er: 4,5 x 3,35 x 3,35 m
Omrører: Nei
Overtrykk: 0,50 bar
Total uttapping: Nei, det er det ikke.
Undertrykk (vakuum): 0,10 bar
Trykktank: Ja
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 27800

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Total høyde: 4 550 mm
Ytre diameter: 3 350 mm

Mer

Isolert: Nei

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor